

# earthBorn Gloss



## 1. What is earthBorn Gloss?

earthBorn Gloss is for interior and exterior use on wood and metal such as windows and doors.

## 2. Colours and product codes

	White	Off White	Ochre	Sand Orange	Bordeaux Red	Stone Green	Slate Grey	Vanilla
750ml	2-3742	9-3022	9-3032	9-3042	9-3052	9-3062	9-3072	9-3082
2.5l	2-3743	9-3023	9-3033	9-3043	9-3053	9-3063	9-3073	9-3083
	Straw	Lemon	Taupe	Lilac	Blush	Sugar Almond	Wedgwood Blue	Wedgwood Green
750ml	9-3092	9-3102	9-3112	9-3122	9-3132	9-3142	9-3152	9-3162
2.5l	9-3093	9-3103	9-3113	9-3123	9-3133	9-3143	9-3153	9-3163

## 3. Coverage

Approximately 10-12 m<sup>2</sup> per litre or 0.08 –0.1 litre per m<sup>2</sup>

## 4. Thinners

earthBorn Natural Thinners

## 5. Properties

earthBorn Gloss has been formulated from traditional paint recipes with a natural oil base. It is a high solids content paint so has excellent covering properties and good flexibility. It has a gloss finish, is weather-resistant and is easy to apply.

## 6. Preparation

Surfaces must be sound, absorbent, dry, clean and free of dust and grease. For new wood, sand and apply earthBorn White Undercoat. (No primer required)

Prime new metal with Red Oxide Primer and apply earthBorn White Undercoat.

Sand all previously painted surfaces and apply earthBorn White Undercoat. Allow to dry and sand again.

## 7. Application

Stir thoroughly before use. earthBorn Gloss can be applied with a brush, roller or spray gun. If applying a second coat allow to dry between coats.

## 8. Drying Time

Depending on the temperature and the Relative Humidity, touch-dry after approximately 3-4 hours but allow 24 hours drying time between coats.

## 9. Cleaning

Tools can be cleaned with Natural Thinners. Wash hands using Hand Cleaner if necessary.

## 10. Storage

Keep containers tightly sealed and store in a cool, dry and frost-free place.

Shelf life is 2 years for unopened containers.

## 11. Safety

Please refer to the Material Safety Data Sheet

## 12. Ingredients

Linoleic acid, processed soya oil, soya-based alkyd, titanium dioxide, isoaliphate, d-lemon, cobalt, zinc and zirconium salts as desiccants.

## 13. Disposal

After being allowed to dry, earthBorn Gloss can be disposed of by normal waste disposal methods. (Refer to local authority guidelines if necessary) It should not be emptied into drains or watercourses.

*Our standard colours are made using a traditional batch process so there may be slight colour variations between batches and the colour chart. Whilst every precaution is taken to ensure colour continuity, please make sure you have sufficient paint from the same batch to complete your work.*

*The user is recommended to test the product on the intended surface to ensure its suitability*



Frodsham Business Centre  
Bridge Lane  
Frodsham  
Cheshire WA6 7FZ  
T: 01928 734171  
F: 01928 731732  
www.earthbornpaints.co.uk