

# Volvox Hard Oil



## 1. Use

Transparent, highly-hardwearing oil treatment for heavily used interior surfaces (e.g. wood floors, doors, stairs, worktops, cork and open-pored stone). Very good penetration properties. Ideally suited for cork & wood surfaces prior to waxing.  
N.B. On light softwood, spotty patches may occur, if so use Volvox High Solids Floor Oil.

## 2. Product Codes

750ml 2-3402  
2.5l 2-3403

## 3. Coverage

20-50ml per sq m; 20-50 sq m per litre depending on the surface properties.

## 4. Colour

Clear, enriching the colour of the wood

## 5. Thinner

Dilute with earthBorn Natural Thinners or Isoparaffin

## 6. Drying Time

Depending on temperature & relative humidity, dry enough not to hold dust after 3 hours. Touch dry after 4-6 hours and ready for sanding and further treatment after 24 hours.

Note: On cork flooring drying times may be longer and the user is advised to test prior to use.

## 7. Properties

Volvox Hard Oil is made from carefully selected premium quality ingredients that cause less harm to the user and the environment (including watercourses) than conventional alternatives.

## 8. Instructions for Use

Do not apply in temperatures below 8°C.

**Preparation:** The surface must be clean, dry, absorbent & grease-free. Sand wood carefully (grain 240-320)

### Application:

Volvox Hard Oil is applied by brush or foam roller. After 5-10 minutes carefully remove excess oil with a lint free cloth, otherwise glossy spots may occur. Sand the first coat when dry (allow 24 hours) and apply further coats as necessary (a droplet of water should 'bead' on the dry surface). Typically 2-3 coats are required. After final coat has dried build up the coating with Volvox WBC Wax.

## 9. Tools

Brush, foam roller.

## 10. Storage

Keep containers tightly sealed and store in a cool but frost-free place. Storage life when unopened approx 9 months under recommended storage conditions

## 11. Ingredients

Linseed oil, tung oil, colophony hardened resin, ricinene stand oil, isoparaffin, anti-skinning agent, lead-free drying agents

## 12. Technical Data

Viscosity: 14 secs  
Solids: ca. 45%  
Finish: matt to satin

## 13. Safety

Product is flammable. Do not smoke whilst working and do not use an unshielded flame. During and after application keep rooms well ventilated. Rags soaked with the product are self-combustible and must be disposed of in a sealed metal container or spread out to dry. Even though non-toxic keep out of the reach of children.

## 14. Disposal

Allow unused oil to dry. Dispose of any product surplus to requirements in accordance with local authority disposal guidelines.

*The user is recommended to test the product on the intended surface to ensure its suitability*



Frodsham Business Centre  
Bridge Lane  
Frodsham  
Cheshire WA6 7FZ  
T: 01928 734171  
F: 01928731732  
[www.earthbornpaints.co.uk](http://www.earthbornpaints.co.uk)