

# Volvox Thin Layer UV Varnish

## 1. Description

Volvox Thin Layer UV-Varnish is a weather-proof, virtually non-drip, protective coating for outdoor wood. It provides good protection against UV-rays.

## 2. Product Codes

750ml 2-3612  
2.5l 2-3613

## 3. Coverage

Depending on surface properties, 80-120 ml per square metre (approx. 8-12 sq m per litre) Two coats are required for optimum results.

## 4. Colour

Clear (almost colourless). When used on dark wood, depending on the light conditions, the product may sometimes appear cloudy

## 5. Thinner

Volvox Isoparaffin

## 6. Drying Times

Dependent on temperature and relative humidity the varnish is dry enough after 6 hours not to hold dust; touch dry after 8 hours and completely dry after 12-24 hours.

## 7. Uses

Designed as a transparent, water-repellent and weather – resistant outdoor protection for wood, especially fascias ( not window frames and doors). Not suitable for wood having immediate contact with the ground.

## 8. Properties

Volvox UV-Varnish Thick Layer is transparent, water-repellent and weather-proof, emphasising the natural wood grain. It is made from non-toxic, natural raw materials. It does not cause static electricity and when used correctly is innocuous to people and the environment

## 9. Instructions for Use

Gel-like consistency. Stir well before use. Do not apply when the temperature is below 8 deg C

### Preparation

The surface should be clean, dry, grease-free, absorbent and sanded. To obtain maximum UV protection, apply two coats

of Volvox UV-Primer ( See Product Information Sheet 2-333) When dry, lightly sand the primed surface.

### Application

Stir well before and whilst applying the product. Apply two coats of Volvox Thin Layer UV Varnish. When the first coat is dry, the wood may be sanded. A brush or suitable spray gun e.g. Airmix, nozzle 13/50°, 60-100 bar may be used.

After use clean the tools with Volvox Isoparaffin

### Note

Outdoor wood may swell up and shrink, depending on humidity. The finished surface should be examined annually and maintained accordingly

## 10. Storage

Keep containers tightly sealed and store in a cool but frost-free place

## 11. Ingredients

Soya alkyd, silicic acid, sheet silicates, anti-skinning agent, lead-free drying agents, titanium dioxide, UV-absorber, micronised iron oxides, isoparaffin

## 12. Technical data

Specific gravity approx 0.769g/cc; Solids ≈ 33%; Viscosity thixotropic

## 13. Safety

The product is flammable. Keep out of the reach of children. Do not breathe fumes/vapour/spray. Avoid contact with skin. In case of fire use carbon dioxide, sand or powder extinguishers. Never use water! If swallowed, seek medical advice immediately and show the container. Special note for working with oils, lacquers and varnishes: The product is flammable. Do not smoke or use naked flames whilst working. Always work in a well-ventilated area. Cloths soaked with the product should not be left lying around – danger of self-ignition. Such cloths should be spread out outdoors to dry or put into sealed metal container.

## 14. Disposal

Allow unused paint to dry. Dispose of any product surplus to requirements safely, according to local authority disposal guidelines.

*The user is recommended to test the product on the intended surface to ensure its suitability*



Frodsham Business Centre  
Bridge Lane  
Frodsham  
Cheshire WA6 7FZ  
T: 01928 734171  
F: 01928 731732  
[www.earthbornpaints.co.uk](http://www.earthbornpaints.co.uk)

Data sheets/Volvox UV Thin Varnish Rev. A Jun05